



panda n-type TOPCon Bifacial Module

600-630 W

MAXIMUM MODULE EFFICIENCY

23.3%

POSITIVE POWER TOLERANCE

0 TO +5 W



IDEAL FOR:

 Utility Projects

BUILT TO LAST


Outstanding Bifaciality | SuperiorYield | Robust Frame

QUALIFICATIONS & CERTIFICATES

- IEC 61215, IEC 61730, CE
- ISO 9001: Quality management systems
- ISO 14001: Environmental management systems
- IEC 62941: Quality system for PV module manufacturing
- ISO 45001: Occupational health and safety management systems
- SA8000 Standard (Social Accountability International)





Munich RE 




0.40% annual power degradation

BACK VIEW (units: mm)



I-V / P-V CURVES



Warning: Read the Installation and User Manual in its entirety before handling, installing, and operating Yingli Solar modules.

MODULE TYPE YLxxxCF66 i/2 (xxx=Pmax)
DIMENSIONS 2382 mm / 1134 mm / 30 mm WEIGHT 33.9 kg FIRE RESISTANCE RATING Class A

Electrical Parameters at Standard Test Conditions (STC*)

Power output-Pmax (W)	600	605	610	615	620	630
Power output tolerances-ΔPmax (W)	0 / + 5	0 / + 5	0 / + 5	0 / + 5	0 / + 5	0 / + 5
Module efficiency-ηm (%)	22.2	22.4	22.6	22.8	23.0	23.3
Voltage at Pmax - Vmpp (V)	40.41	40.72	41.03	41.34	41.65	42.27
Current at Pmax-Impp (A)	14.85	14.86	14.87	14.88	14.89	14.91
Open-circuit voltage-Voc (V)	48.42	48.71	49.01	49.31	49.61	50.21
Short-circuit current-Isc (A)	15.77	15.80	15.83	15.86	15.89	15.95

*STC: 1000 W·m⁻² irradiance, 25°C cell temperature, AM 1.5.

Electrical Parameters at Nominal Operating Cell Temperature (NOCT*)

Power output-Pmax (W)	456	460	464	468	472	479
Voltage at Pmax - Vmpp (V)	38.55	38.84	39.14	39.44	39.73	40.32
Current at Pmax-Impp (A)	11.84	11.85	11.86	11.86	11.87	11.89
Open-circuit voltage-Voc (V)	45.98	46.26	46.54	46.83	47.11	47.68
Short-circuit current-Isc (A)	12.71	12.73	12.75	12.78	12.80	12.85

*NOCT: open-circuit module operation temperature at 800 W·m⁻² irradiance, 20°C ambient temperature, 1 m·s⁻¹ wind speed.

Bifacial Electrical Parameters at Standard Test Conditions (BNPI*)

Power output-Pmax (W)	665	670	676	682	687	698
Voltage at Pmax - Vmpp (V)	40.41	40.72	41.03	41.34	41.65	42.27
Current at Pmax-Impp (A)	16.45	16.46	16.48	16.49	16.50	16.52
Open-circuit voltage-Voc (V)	48.42	48.71	49.01	49.31	49.61	50.21
Short-circuit current-Isc (A)	17.47	17.51	17.54	17.57	17.61	17.67

*1000W·m⁻² on the front side and 135W·m⁻² on the back side, 25°C cell temperature, AM 1.5. Bifaciality coefficient is 80% ± 5%.
 φPmax = 80%, φIsc = 80% and φVoc = 99% with tolerance 5% for reference. Measurement tolerance: Pmax ±3%, Voc ±3% and Isc ±3%.

Thermal Characteristics

Nominal operating cell temperature-NOCT(°C)	42±2
Temperature coefficient of Pmax-γ(% / °C)	-0.29
Temperature coefficient of Voc-β(% / °C)	-0.24
Temperature coefficient of Isc-α(% / °C)	0.042

Packaging Specifications

Number of modules per pallet	36
Number of pallets per 40' container	20
Packaging box dimensions (L / W / H)	2400 mm / 1110 mm / 1245 mm
Box weight	1280 kg

Operating Conditions

Max. system voltage	1500 Vdc
Max. series fuse rating*	30 A
Operating temperature range	-40°C ~ 85°C
Max. static load, front (e.g., snow)	5400 Pa
Max. static load, back (e.g., wind)	2400 Pa
Max. hailstone impact (diameter / velocity)	25 mm / 23 m·s ⁻¹

*Do not connect fuse in combiner box with two or more strings in parallel connection.

Construction Materials

Cell (material / quantity)	n-type monocrystalline silicon / 6 x 22
Glass (thickness)	2.0 mm / 2.0 mm
Frame (material)	Anodised aluminum alloy
Junction box (type / protection degree)	3 bypass diodes / ≥ IP68
Plug connector (type)	Staubli EVO2 or Yitong YT18-01 or Renhe RHC2 or HY-H4
Cable (length / cross-sectional area)	±1400 mm or customised length / 4 mm ²

- Proudly manufactured in China.
- Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed.
- The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.

Visit Our Website

