



panda n-type TOPCon Bifacial Module

610-635 W

MAXIMUM MODULE EFFICIENCY

22.7%

POSITIVE POWER TOLERANCE

0 TO +5 W



IDEAL FOR:


Utility Projects

NEVER SETTLE FOR LESS



Outstanding Bifaciality | SuperiorYield | Robust Frame

QUALIFICATIONS & CERTIFICATES


IEC 61215, IEC 61730, CE
ISO 9001: Quality management systems
ISO 14001: Environmental management systems
IEC 62941: Quality system for PV module manufacturing
ISO 45001: Occupational health and safety management systems
SA8000 Standard (Social Accountability International)



BACK VIEW (units: mm)



I-V / P-V CURVES



Warning: Read the Installation and User Manual in its entirety before handling, installing, and operating Yingli Solar modules.

MODULE TYPE YLxxxCF78 e/2 (xxx=Pmax)

DIMENSIONS 2465 mm / 1134 mm / 30 mm **WEIGHT** 35.0 kg **FIRE RESISTANCE RATING** Class A

Electrical Parameters at Standard Test Conditions (STC*)

Power output-Pmax (W)	610	615	620	625	630	635
Power output tolerances-ΔPmax (W)	0 / + 5	0 / + 5	0 / + 5	0 / + 5	0 / + 5	0 / + 5
Module efficiency-ηm (%)	21.8	22.0	22.2	22.4	22.5	22.7
Voltage at Pmax - Vmpp (V)	45.59	45.77	45.95	46.13	46.31	46.49
Current at Pmax-Impp (A)	13.39	13.44	13.50	13.55	13.61	13.66
Open-circuit voltage-Voc (V)	55.30	55.44	55.58	55.72	55.86	56.00
Short-circuit current-Isc (A)	14.04	14.12	14.20	14.28	14.36	14.44

*STC: 1000 W·m⁻² irradiance, 25°C cell temperature, AM 1.5.

Electrical Parameters at Nominal Operating Cell Temperature (NOCT*)

Power output-Pmax (W)	464	468	472	475	479	483
Voltage at Pmax - Vmpp (V)	43.49	43.66	43.83	44.01	44.18	44.35
Current at Pmax-Impp (A)	10.68	10.72	10.76	10.80	10.85	10.89
Open-circuit voltage-Voc (V)	52.51	52.65	52.78	52.91	53.05	53.18
Short-circuit current-Isc (A)	11.31	11.38	11.44	11.51	11.57	11.63

*NOCT: open-circuit module operation temperature at 800 W·m⁻² irradiance, 20°C ambient temperature, 1 m·s⁻¹ wind speed.

Bifacial Electrical Parameters at Standard Test Conditions (BNPI*)

Power output-Pmax (W)	676	682	687	693	698	704
Voltage at Pmax - Vmpp (V)	45.59	45.77	45.95	46.13	46.31	46.49
Current at Pmax-Impp (A)	14.84	14.89	14.96	15.01	15.08	15.14
Open-circuit voltage-Voc (V)	55.30	55.44	55.58	55.72	55.86	56.00
Short-circuit current-Isc (A)	15.56	15.64	15.73	15.82	15.91	16.00

*1000W·m⁻² on the front side and 135 W·m⁻² on the back side, 25°C cell temperature, AM 1.5. Bifaciality coefficient is 80% ± 5%.

φPmax = 80%, φIsc = 80% and φVoc = 99% with tolerance ±5% for reference. Measurement tolerance: Pmax ±3%, Voc ±3% and Isc ±3%.

Thermal Characteristics

Nominal operating cell temperature-NOCT(°C)	42±2
Temperature coefficient of Pmax-γ(°C)	-0.29
Temperature coefficient of Voc-β(°C)	-0.24
Temperature coefficient of Isc-α(°C)	0.042

Operating Conditions

Max. system voltage	1500 Vdc
Max. series fuse rating*	30 A
Operating temperature range	-40°C ~ 85°C
Max. static load, front (e.g., snow)	5400 Pa
Max. static load, back (e.g., wind)	2400 Pa
Max. hailstone impact (diameter / velocity)	25 mm / 23 m·s ⁻¹

*Do not connect fuse in combiner box with two or more strings in parallel connection.

Packaging Specifications

Number of modules per pallet	36
Number of pallets per 40' container	16
Packaging box dimensions (L / W / H)	2480 mm / 1110 mm / 1245 mm
Box weight	1320 kg

Construction Materials

Cell (material / quantity)	n-type monocrystalline silicon / 6 x 26
Glass (thickness)	2.0 mm / 2.0 mm
Frame (material)	Anodised aluminum alloy
Junction box (type / protection degree)	3 bypass diodes / IP68
Plug connector (type)	Staubli EVO2 or Yitong YT18-01 or Renhe RHC2 or HY-H4
Cable (length / cross-sectional area)	±1200 mm / 4 mm ²



Visit Our Website

- Proudly manufactured in China.
- Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed.
- The data does not refer to a single module and they are not part of the offer, they only serve as a comparison to different module types.